

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 July 2001 (05.07.2001)


PCT

(10) International Publication Number
WO 01/48856 A1

- (51) International Patent Classification⁷: **H01P 7/10**
- (21) International Application Number: **PCT/AU00/01579**
- (22) International Filing Date:
21 December 2000 (21.12.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PQ 4877 23 December 1999 (23.12.1999) AU
- (71) Applicants (*for all designated States except US*): **POSEIDON SCIENTIFIC INSTRUMENTS PTY LTD** [AU/AU]; Unit 1, 95 Queen Victoria Street, Fremantle, Western Australia 6160 (AU). **THE UNIVERSITY OF WESTERN AUSTRALIA** [AU/AU]; Stirling Highway, Nedlands, Western Australia 6907 (AU).
- (72) Inventor; and
(75) Inventor/Applicant (*for US only*): **TOBAR, Michael, Edmund** [AU/AU]; The University of Western Australia, Department of Physics, Mounts Bay Road, Crawley, Western Australia 6009 (AU).
- (74) Agent: **WRAY & ASSOCIATES**; 239 Adelaide Terrace, Perth, Western Australia 6000 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: **MULTI-LAYER MICROWAVE RESONATOR**



(57) Abstract: A multi-layer microwave resonator (10) comprises a cavity (12) having an inner surface formed from an electrically conductive material. Pieces (16a - 16e) of dielectric materials stacked on top of each other form a contiguous body (14) that is provided in the cavity (12). The dielectric materials of the pieces (16a - 16e) are chosen such that the dielectric constant of the pieces (16a - 16e) alternate between a relatively high dielectric constant and a relatively low dielectric constant.

WO 01/48856 A1

WO 01/48856 A1



IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *With international search report.*